

Vaccine & Pharmacy Refrigerators

LIEBHERR pharmacy fridges are QCPP compliant, independently tested in accordance with the Australian Government "Strive for 5" vaccine storage guidelines and QCCP standard which requires temperatures to be stable between 2°C and 8°C.

LIEBHERR

Pharmacy refrigeration and UPS pack
Scientific and Healthcare





SRFvh 4011



SRFvh 5511



LKUv 1613

Gross/net capacity	
Ext. dimensions in mm (w/d/h)	
Int. dimensions in mm (w/d/h)	
Energy consump. 365 days	
Ambient temperature range	
Refrigerant	
Temperature Range	
Temperature display	
Defrosting	
Cooling system	
Interior Light	
Fault: warning signal	
Adjustable shelving	
Lock	
Self-closing door	
Door hinges	
Gross/net weight	

420 / 297 litre
597 / 654 / 1884
460 / 423 / 1660
389 kWh
+10 °C to +35 °C
R 600a
+3°C to +16°C
External digital
Automatic
forced-air / automatic
Vertical LED light strip
visual and audible
9
Fitted
Yes
right, reversible
86 / 80 kg

588 / 440 litre
747 / 769 / 1793
606 / 536 / 1460
360 kWh
+10 °C to +35 °C
R 600a
+3°C to +16°C
External digital
Automatic
forced-air
Vertical LED light strip
visual and audible
9
Fitted
Yes
right, reversible
111 / 98 kg

152 / 132litre
601 / 618 / 820
440 / 435 / 670
369kWh
+10 °C to +35 °C
R 600a
+3°C to +16°C
External digital
Automatic
Forced-air
Horizontal LED
Visible and audible
3
fitted
Yes
Right/reversible
45 / 43kg

FEATURES

Antimicrobial Handle
12 Hour Battery Back Up Controller
"One Touch" Min and Maxreading
Touch/Swipe Digital Controller
Energy Efficient
+2 °C Safety Device
5 years of data storage
Integrated Data Logger/USB interface

Antimicrobial Handle
12 Hour Battery Back Up Controller
"One Touch" Min and Maxreading
Touch/Swipe Digital Controller
Energy Efficient
+2 °C Safety Device
5 years of data storage
Integrated Data Logger/US Binterface

Convenient undercounter size
Self-Closing Door
45kg Shelf Loading
Electronic Controller
Energy Efficient
+2 °C Safety Device
Temperature alarm
RS485 interface



When a SRFvh 4011 or SRFvh 5511 is combined with a CSCT-2000-KIT, holding times of up to 32 hours can be achieved between 2°C -8°C. This assists in a reduction of stock loss and insurance claims.

